



LED DISPLAYS:ELC-5304 SERIES

ELECTRICAL AND OPTICAL CHARACTERISTICS (Ta=25℃)

Part No.	Emitted Color	Peak Wave Length	Epoxy Color	Surface Color	$\Delta\lambda$ (nm)	Pd (mW)	If (mA)	Peak (mA)	Vf(V)		IV(mcd)	
									Min	Max	Min	Max
ELC-5304R	Red	620-630	White	Black	10	35	20	60	1.8	2.0	82	92
ELC-5304O	Orange	600-610	White	Black	10	35	20	60	1.8	2.0	85	95
ELC-5304Y	Yellow	585-595	White	Black	10	35	20	60	1.8	2.0	88	98
ELC-5304G	Olivine	565-575	White	Black	10	35	20	60	1.8	2.0	10	20
ELC-5304GG	Emerald	515-525	White	Black	10	55	20	60	2.6	2.8	215	225
ELC-5304B	Blue	460-470	White	Black	10	55	20	60	2.6	2.8	15	25
ELC-5304W	White	-	-	Black	-	55	20	60	2.6	2.8	-	-

ABSOLUTE MAXIMUM RATINGS (Ta=25℃)

Reverse Voltage	Reverse Current (V _R =5V)	Operating Temperature Range	Storage Temperature Range	Lead Soldering Temperature
5V	20 μ A	-20℃~+80℃	-30℃~+80℃	255℃ For 3 seconds

PACKAGE DIMENSION (Unit: millimeters, Tolerance : ± 0.25 mm)

